

9300 Series Submersible DC Pump 24 VDC Submersible Pump



Model	9325-043-101					
Description	24VDC Submersible Pump for potable water wells 1/2" Hose Barb discharge port 50 mesh SS inlet screen					
Vertical Lift (feet)	20	60	100	140	180	230
Vertical Lift (meters)	6.1	18.3	30.5	42.7	54.9	70.1
Flow (GPH)	111	105	100	93	87	79
Flow (LPH)	420	398	379	352	329	300
Solar Array (Min Watts)	58	78	99	115	135	155
Current Amps	1.7	2.3	2.9	3.5	4.0	4.6

SHURflo®

First in Fluid Innovation

9300 DC Pump Controller



Model	902-200
Max. Array Input Voltage (24V)	45V
Max. Array Input Voltage (12V)	N/A
Min. Startup Voltage (24V)	25V
Min. Startup Voltage (12V)	12.5V
Shutdown Voltage	28V
Max. Output Current	7 Amps



First in Fluid Innovation

9300 DC Pump Controller



Model	902-100
Max. Array Input Voltage (24V)	45V
Max. Array Input Voltage (12V)	N/A
Min. Startup Voltage (24V)	25V
Min. Startup Voltage (12V)	N/A
Shutdown Voltage	28V
Max. Output Current	5 Amps